



1520EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1520EU
Standard



1524
With Padded Dividers



1520NF
No Foam



1520WF
With Foam

DIMENSIONS

Interior (L×W×D)	17.68 x 12.53" x 6.73 (44.9 x 31.8 x 17.1 cm)
Exterior (L×W×D)	19.65 x 15.49" x 7.53 (49.9 x 39.3 x 19.1 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	4.93" (12.5 cm)
Total Depth	6.72" (17.1 cm)
Int Volume	0.86 ft³ (0.024 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body
Purge Vent

ABS
3 Micron Hydrophobic Non-Woven

COLOURS

Black
Silver

Desert Tan
Yellow

Orange

OD Green

WEIGHT

Weight With Foam 9.35 lbs (4.2 kg)
Weight Empty 8.29 lbs (3.8 kg)
Buoyancy 63.00 lbs (28.6 kg)
Master Pack Weight 23.30 lbs (10.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280

OTHER

Master Pack 2
Nameplate yes
Military yes

ACCESSORIES



1508
Photographer's Lid Organizer



1509
Lid Organizer



1521
3 pc. Replacement Foam Set



1523
Replacement O-ring



1525
Padded Divider Set



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1520PF
Special Application Panel
Frame

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 10-20-22